

CM TWIN BOOSTER

CM twin Booster set consists of two identical Grundfos CM pumps connected in parallel and mounted on a common base frame and a control cabinet incorporating motor protection and controller.



PUMPSET FEATURES

- Non self priming, horizontal, multistage centrifugal pump
- CM Twin Booster sets are supplied as complete preassembled and tested system (Without pressure tank)
- Installation friendly: Compact, mounted on a common frame, including all necessary accessories and internal piping
- Reliability of supply: Multi-pump operation maintains supply, even in the event of one pump failure
- Paint application by electrophoresis gives the motor and pump CI parts excellent corrosion resistance
- Simple control and alteration between pumps, dry running protection, built in relay for ensuring constant and steady operation
- Enclosure Class: IP 54
- Insulation Class: F
- Automatic start / stop upto 100 Times/hour
- Quiet operation
- Anti-corrosive coating on cast iron parts. Excellent corrosion resistance

APPLICATIONS

- Large houses
- Domestic building
- Cottage and villas
- Hotels
- Hospitals
- Schools
- Industrial Plants

MATERIAL OF CONSTRUCTION

Pump shaft	AISI 304
Chamber	AISI 304
Impeller	AISI 304
Suction chamber	Cast iron
Manifold	MS galvanized /AISI 304 (on request)

Twin system includes:

- Suction and discharge manifolds
- Isolating valves
- Non- return valves
- Pressure gauge
- Pressure switch
- Grundfos Controller CS 201 (1 phase) or Multi S (3 Phase)
- Base frame


Controls:

Grundfos controller CS 201 (Single phase) or Multi S (Three phase) is used to control these pumps. Few of the features of the controllers:


- Automatically cascade control of the pumps by means of two pressure switches
- Automatic pump changeover at any start / stop cycle
- Pump and system monitoring functions:
 - ♦ Short circuit protection by means of fuses
 - ♦ Motor overload protection by means of thermal switch built into the motor (1ph only)
 - ♦ Dry running protection by means of an additional pressure switch or level switch (Accessory)
 - ♦ Start and stop delays to prevent simultaneous start / stopping of the two pumps (For 3 phase only)
 - ♦ Stop delay after reaching the respective cut-out pressure (For 3 phase only)

Performance curves - Single pump

CM3



CM5



GRUNDFOS PUMPS INDIA PRIVATE LTD.

Toll free: 1800 - 345 - 4555. Email: salesindia@grundfos.com

- Chennai: 0 9840944720 • Mumbai: 0 9987264514 • New Delhi: 0 9910005316
- Bangalore: 0 9945684103 • Hyderabad: 0 9963007733 • Kolkata: 0 9830345072
- Pune: 020 - 32403640 • Ahmedabad: 079 - 40063618 • Maldives: 0 9607793720
- Kochi: 0 9895758124 • Surat: 0 9725045271 • Chandigarh: 097791 25824
- Indore: 0 9893098763 • Jaipur: 0 9829036168 • Madurai: 0 9940112407 • Nagpur: 0 9970182577
- Coimbatore: 0 9791011130 • Raipur: 0 99935 83536 • Bhubaneswar: 0 99370 34044

